

Technical Data



SILICONE LUBRICANT GENERAL PURPOSE LUBRICANT



SILICONE LUBRICANT is a general purpose, medium duty silicone lubricant, which exhibits excellent anti-stick and slip properties.

Ideal for use where a clean, colourless lubricant is required. Safe to use on wood, glass, fabrics, metals, most plastics, rubbers and hard surfaces.

APPLICATIONS

Perfect for use on numerous different applications, including:

- Sewing Machines
- Cutting Table
- Forms a colourless, non-staining film
- Processing Equipment
- Laying-up Areas
- Cutting Knives , Blades and Guillotines
- Foam Conversion
- Chutes and Conveyors
- Paper and Textile
- Anywhere that sticking or fusing causes problems
- Can also be used as a mould release agent

Apply a light, even coating from 9" - 12" (25 - 30 cm). Remove any overspray with a clean cloth and re-apply as necessary.

TECHNICAL DATA

- Appearance : Clear, colourless liquid
- Odour : Hydrocarbon solvent
- SG @ 25°C : 0.709
- Pressure @ 25°C : 3.5 Bar
- Discharge rate : 0.9 g/sec
- Temperature range : Operational from -50°C to +200°C
- Solubility : Soluble in solvents, insoluble in water
- Flammability : Classified as extremely flammable under current EC Regulations
- Flashpoint : Not applicable in sealed aerosol

Packaging : 500 ml aerosol (12 per carton)

STORAGE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 72 months with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

HEALTH AND SAFETY

Health and Safety sheet available separately.

TECHNICAL SERVICE

CRC Industries UK Ltd provides a technical support service and maintains a constant programme of research and development. We are able to assist customers by specific product development to meet particular requirements.

MISREPRESENTATION ACT 1967 TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

PRODUCER:

CRC Industries UK Ltd, Wylde Road, Bridgwater, Somerset, TA6 4DD, UK.